


Battery Combi Tool

Battery Combi Tool





Description

Application

One Tool for spreading, cutting and pulling.

Traffic accident, collapsed building, earthquake etc.

Features

- ➤ With its own power, no external power source, no tube, zero emissions, greener and healthier.
- ➤ High performance, low noise, original import battery, plug and play;
- ➤One-key operate, instant-on;
- ➤ The switch and lighting adopt split-type design, double conversion on demand;
- ➤LED indicator can show the stock of the battery timely
- The handle with the configuration of lamp which can provide light, it's convenient for night operation
- ➤ The star-shaped design of hand valve makes the operation more convenient and accurate.
- ➤ Multifunctional auxiliary work head with anti-skid design, easy for narrow space operate
- ➤ The manual reversing valve makes operation convenient and more accurate
- ➤ Adopts Bi-directional hydraulic lock with self-lock function
- ➤ Cutting edge adopts collapsing &splashing prevention design and protective jacket

Specification

Model	ECT-370	
Rated Working Pressure	72MPa(720bar)	10440psi
Spreader Force	60KN	11240 lbf
Cutting Force	390KN	87675 lbf
Blade Distance	368mm	14.5in
Traction Power	61KN	13713 lbf
Max. Cutting Capacity(Q235 steel)	Ø32mm	Ø1.38in
Weight with Battery	19.6Kg	43.2 lbs
Dimension	966x243x256mm	38x9.6x10in
Power Supply	Battery DC 28V 5.0 Ah	
Temperature Range	-20°C −+55°C	